

Footy Swing Rigs

A rig Development Details & Cutting list

RIG	Just'in*	550 (A)	500 (aB)	400 (aC)	300 (aD)	Material
Mast Length	680	598	530	460	400	3mm x 2mm id Carbon tube
Fore yard	175	170	148	133	115	
Aft Yard	275	280	240	205	178	
Jib Boom	195	195	167	143	125	1.2mm (18swg) hard SS wire
Head Crane mast to wind indicator	59	40	33	27	22	1.8mm (16swg) hard SS wire
MAINSAILS						
Head	70	50	43	37	32	Lightweight plastic bin liners
Luff	625	560	482	414	356	
Leech	663	588	506	435	374	
Roach	37	50	43	37	32	
Batten Length	90	110	95	81	70	
Aft head to batten	160	212	182	157	135	
Foot (8mm round)	275	281	242	208	179	
HEADSAILS						
Head	11	11	11	11	11	Lightweight plastic bin liners
Luff	575	515	443	381	328	
Leech	570	497	427	368	316	
Foot (3 mm round)	200	200	172	148	127	

WIRE COMPONENTS		
each Rig requires the following components		
1 No	Yard fitting	2mm (14swg) hard stainless wire bent to loop
1 No	Foresail/down haul adjuster	0.5mm (24swg) hard stainless wire bent
1 No	Mainsail clew attachment	0.5mm (24swg) hard stainless wire bent
2 No	Bowsies	0.5mm (24swg) hard stainless wire bent

* in the UK we voluntarily use the experimental big rig template, as it's name suggests the "Just'in" rig is designed to maximise the sail area and yet fit within this rig template.