

# Footy Swing Rigs

## Details & Cutting list

RIG	Just'in*	550 (A)	500 (B)	400 (C)	300 (D)	Material
<b>Mast Length</b>	680	598	528	427	334	3mm x 2mm id Carbon tube
<b>Fore yard</b>	175	170	137	130	130	
<b>Aft Yard</b>	275	280	235	225	220	
<b>Jib Boom</b>	195	195	153	153	153	1.2mm (18swg) hard SS wire
<b>Head Crane</b> mast to wind indicator	59	40	40	40	40	1.8mm (16swg) hard SS wire
<b>MAINSAILS</b>						
<b>Head</b>	70	50	50	50	50	Lightweight plastic bin liners
<b>Luff</b>	625	560	480	382	283	
<b>Leech</b>	663	588	498	400	310	
<b>Roach</b>	37	50	40	40	40	
<b>Batten Length</b>	90	110	90	90	90	
<b>Aft head to batten</b>	160	212	140	125	110	
<b>Foot</b> (8mm round)	275	281	240	230	223	
<b>HEADSAILS</b>						
<b>Head</b>	11	11	11	11	11	Lightweight plastic bin liners
<b>Luff</b>	575	515	431	360	270	
<b>Leech</b>	570	497	422	336	242	
<b>Foot</b> (3 mm round)	200	200	161	161	161	

<b>WIRE COMPONENTS</b>		
each Rig requires the following components		
1 No	Yard fitting	2mm (14swg) hard stainless wire bent to loop
1 No	Foresail/down haul adjuster	0.5mm (24swg) hard stainless wire bent
1 No	Mainsail clew attachment	0.5mm (24swg) hard stainless wire bent
2 No	Bowsies	0.5mm (24swg) hard stainless wire bent

\* in the UK we voluntarily use the experimental big rig template, as it's name suggests the "Just'in" rig is designed to maximise the sail area and yet fit within this rig template.